



# RL19

## **Chassis & Frame:**

- Quality Heavy-Duty Steel Construction
- Powder Coated
- Built in the USA

## **Engine and Drive Train:**

- Engine -
- Final Tier 4 and EU Stage 5 Compliant
  - 4 Cylinder 47.6hp Diesel Engine

- Main Feed Belt
- Direct Hydraulic Drive

## **Steel Hoppers:**

- Heavy-Duty Steel Sheeting
- Fully Powder Coated
- 10' Wide Clamshell Hoppers

## **Feed Conveyor:**

- Heavy-Duty Abrasive & Impact Resistant Belt
- 36" Cleated Feed Belt
- Hydraulically Powered
- Height Adjustable

## **Weight & Dimensions:**

\*Specifications may vary upon options/packages

Tow Weight

- Approx. 7,000 lbs

Tow Length

- 22

Operational Length

- 20'

Tow Height

- 8' 7"

Operational Clearance Height

- 12' @ 30 Degrees

## **Electrical System**

12 or 24 VDC

- Yanmar CANplus® Electronic Engine Controls

## **Production:**

\*Volumes vary upon material

- 4-6 Tons of 1" Rock per Minute
- 6-10 Yards of Organic Material per Minute

## **Optional Equipment:**

- Radio & Receiver Remote Controlled Package
- Funnel Hopper Attachment