



EZ FLOW

Chassis & Frame:

Available in one size:
EZ Flow 18 - 18 Cubic Yards
*Chassis is customer specified

Hopper Body

- 450 HARDOX™ Steel
- Spring Body Mounted
- Powder Coated Finish
- Electric Swing-Arm Tarp
- Vibrator

Weight & Dimensions:

Weight - Approx. 11,000 lbs
Capacity - 18 Cubic Yards
Operational Length - 26' 2"
Tow Width - 8' 4"
Tow Height - 7'
*Specifications may vary upon options/packages

Hydraulic System

- PTO Mounted 500 BAR Closed Loop Hydraulic Pump Integrated with 3,500 PSI Rated Rear Pump
- Pressure & Return Filtration Systems
 - Pressure Filter Rating - 10 Microns
 - Return Filter Rating - 10 Microns
- HAWE Proportional Valves
- High Pressure Hoses & Fittings: 2,000 - 6,000 PSI

Feed Conveyor:

- Heavy-Duty 36" 330 3-Ply Abrasive & Impact Resistant Belt
- Hydraulically Powered
- Planetary Gear Main Driver
- 2.25" Pitch Pintle Chain
 - 52,000 lbs. Pulling Strength
- Rear Leveling Gate

Placing Conveyor:

- HD 14" Abrasive & Impact Resistant Belt (1/2" W x 1/2" H x 8 1/4" OAW on 6" Centers)
 - Tube Steel Design
 - Hydraulic Drive Super-Shield™
 - High Performance Rear Mounted Direct Drive
 - Patented Worm Gear PC Swing
- Performance Specifications:
- FPM - 4,400-4,600
 - MPH - 47-51
 - Volume - 2-3 Yards Per Minute
 - Distance - Up to 120'

Electrical System:

- 12 or 24 VDC
- OMNEX Radio & Receiver Control Package
 - Wireless Remote Controlled Placing
 - Maximum Effective Range - 900 ft @ 2.4 GHz
 - Equipped with Frequency Hopping Spread Spectrum (FHSS) Technology
 - Frequency Hopping @ 50 Non-Overlapping Channels in 100kHz Intervals (100,000 Times per Second)

Optional:

- Chassis
- Rear Fenders [Poly, Aluminum or Stainless Steel]
 - Tool Box [Aluminum or Stainless Steel]
 - Remote Control/Wireless Ground Drive System
 - Motion Alarm
- Hopper
- Pull Tarp
 - PC Performance Package
 - Trenching Attachment