



RL26HD

Chassis & Frame:

- Quality Heavy-Duty Steel Construction
- Powder Coated
- Built in the USA

Engine and Drive Train:

Engine -

- Yanmar® Tier IV Liquid Cooled Turbo Diesel Engine
- Maximum Output: 68.5 HP @ 2,500 RPM

Drive Train

- No Drive

Main Feed Belt

- Direct Hydraulic Drive

Production:

- *Volumes vary upon material
- 4-6 Tons of 1" Rock per Minute
- 10-15 Yards of Organic Material per Minute

Steel Hoppers:

- Heavy-Duty Steel Sheeting
- Fully Powder Coated
- 10' 1.5" Wide Clamshell Hoppers

Feed Conveyor:

- Heavy-Duty Abrasive & Impact Resistant Belt
- 48" Feed Belt
- Hydraulically Powered
- Height Adjustable

Weight & Dimensions:

*Specifications may vary upon options/packages

Tow Weight

- Approx. 10,520 lbs

Tow Length

- 29' 9"

Operational Length

- 26'

Tow Width

- 100"

Tow Height

- 10' 1"

Operational Clearance Height

- 12' 4" @ 28 Degrees

Electrical System

12 or 24 VDC

- Yanmar CANplus® 600 Electronic Engine Controls

Optional Equipment:

- Clamshell Hopper Extensions
- AT7 Hitch