



# RL34

## Chassis & Frame:

- Quality Heavy-Duty Steel Construction
- Powder Coated
- Built in the USA

## Engine and Drive Train:

### Engine -

- Yanmar® Tier IV Liquid Cooled Turbo Diesel Engine
- Maximum Output: 68.5 HP @ 2,500 RPM

### Drive Train

- No Drive

### Main Feed Belt

- Direct Hydraulic Drive

## Steel Hoppers:

- Heavy-Duty Extendable Hopper
- Maximum Extendable Width: 10' 7.5"
- Folded Width: 102"
- Fully Powder Coated
- 23" Wide Exposed Cross-Feed Hopper Conveyors

## Feed Conveyor:

- Heavy-Duty Abrasive & Impact Resistant Belt
- 36" Feed Belt [ Smooth or Cleated ]
- Hydraulically Powered
- Height Adjustable

## Weight & Dimensions:

\*Specifications may vary upon options/packages

### Tow Weight

- Approx. 10,000 lbs

### Tow Length

- 28' 1"

### Operational Length

- 34'

### Tow Width

- 102"

### Tow Height

- 9' 7"

### Operational Clearance Height

- 16' 1.5" @ 30 Degrees | 15' @ 28 Degrees

## Electrical System

12 or 24 VDC

- Yanmar CANplus® 600 Electronic Engine Controls

## Production:

\*Volumes vary upon material

- 4-6 Tons of 1" Rock per Minute
- 6-10 Yards of Organic Material per Minute